

	Type	L #	Hits	Search Text
1	BRS	L1	534	348/231.99-231.9.ccls.
2	BRS	L2	173	1 and resolution

**DBs**

---

**US-PGPUB; EPO; JPO; DERWENT; IBM\_TDB**

---

**US-PGPUB; EPO; JPO; DERWENT; IBM\_TDB**

---

[> home](#) [> about](#) [> feedback](#) [> login](#)

US Patent &amp; Trademark Office

## Search Results

Search Results for: [display<AND>((camera and memory and resolution and compression) )]

Found 142 of 105,850 searched. → Rerun within the Portal

Search within Results

[> Advanced Search](#) [> Search Help/Tips](#)

Sort by: Title Publication Publication Date Score Binder

Results 1 - 20 of 142 short listing

Prev  
Page

1 2 3 4 5 6 7 8

Next  
Page

- 1** A video-based rendering acceleration algorithm for interactive walkthroughs 87%  
Andrew Wilson , Ming C. Lin , Boon-Lock Yeo , Minerva Yeung ,  
Dinesh Manocha  
Proceedings of the eighth ACM international conference on Multimedia  
October 2000

We present a new approach for faster rendering of large synthetic environments using video-based representations. We decompose the large environment into cells and pre-compute *video based impostors* using MPEG compression to represent sets of objects that are far from each cell. At runtime, we decode the MPEG streams and use rendering algorithms that provide nearly constant-time random access to any frame. The resulting system has been implemented and used for an interactive walkthrough ...

- 2** QuickTime VR: an image-based approach to virtual environment navigation 87%



Shenchang Eric Chen

Proceedings of the 22nd annual conference on Computer graphics and interactive techniques September 1995

- 3** Computing curricula 2001 85%



Journal of Educational Resources in Computing (JERIC) September 2001

- 4** Survey of personal interactive multimedia technologies 84%



Chingshun Cheng , C. Jinshong Hwang

Proceedings of the 19th annual conference on Computer Science April 1999

- 5** Multiple viewpoint rendering 83%



Michael Halle

Proceedings of the 25th annual conference on Computer graphics and interactive techniques July 1998

- 6** Managing the storage and battery resources in an image capture device (digital camera) using dynamic transcoding 82%



Surendar Chandra , Carla Schlatter Ellis , Amin Vahdat

Proceedings of the third ACM international workshop on Wireless mobile multimedia August 2000

Advances in hardware imaging technology and user demand for convenient mobile electronic image capture are fueling the development of inexpensive image capture devices that can acquire images rivaling the image quality of photographic film. Improvements in the hardware imaging technology have to be matched with intelligent image storage mechanisms that are aware of local storage and battery constraints. In this paper, we explore using a dynamic, informed image transcoding technique to manag ...

- 7** Deep shadow maps 82%




Tom Lokovic , Eric Veach

Proceedings of the 27th annual conference on Computer graphics and interactive techniques July 2000


We introduce deep shadow maps, a technique that produces fast, high-quality shadows for primitives such as hair, fur, and smoke. Unlike traditional shadow maps, which store a single depth at each pixel, deep shadow maps store a representation of the

fractional visibility through a pixel at all possible depths. Deep shadow maps have several advantages. First, they are prefiltered, which allows faster shadow lookups and much smaller memory footprints than regular shadow maps ...


**8** Crowd modelling in collaborative virtual environments 82%

 Soraia R. Musse , Christian Babski , Tolga Capin , Daniel Thalmann  
Proceedings of the ACM symposium on Virtual reality software and technology 1998 November 1998


**9** Hierarchical view-dependent structures for interactive scene 82%

 manipulation  
Normand Brière , Pierre Poulin  
Proceedings of the 23rd annual conference on Computer graphics and interactive techniques August 1996

**10** CMIFed: a transportable hypermedia authoring system 82%


 Lynda Hardman , Guido van Rossum , Jack Jansen , Sjoerd Mullender  
Proceedings of the second ACM international conference on Multimedia October 1994

**11** Light field mapping: efficient representation and hardware 82%

 rendering of surface light fields  
Wei-Chao Chen , Jean-Yves Bouguet , Michael H. Chu , Radek Grzeszczuk  
ACM Transactions on Graphics (TOG) , Proceedings of the 29th annual conference on Computer graphics and interactive techniques July 2002  
Volume 21 Issue 3

A light field parameterized on the surface offers a natural and intuitive description of the view-dependent appearance of scenes with complex reflectance properties. To enable the use of surface light fields in real-time rendering we develop a compact representation suitable for an accelerated graphics pipeline. We propose to approximate the light field data by partitioning it over elementary surface primitives and factorizing each part into a small set of lower-dimensional functions. We show th ...

**12** Plenoptic stitching: a scalable method for reconstructing 3D 82%

 interactive walk throughs  
Daniel G. Aliaga , Ingrid Carlbom  
Proceedings of the 28th annual conference on Computer graphics and interactive techniques August 2001

Interactive walkthrough applications require detailed 3D models to give users a sense of immersion in an environment. Traditionally these models are built using computer-aided design tools to define geometry and material properties. But creating detailed models is time-consuming and it is also difficult to reproduce all geometric and photometric subtleties of real-world scenes. Computer vision attempts to alleviate this problem by extracting geometry and photogrammetry from images of the real ...

**13** Streaming QSplat: a viewer for networked visualization of large, 82%



dense models

Szymon Rusinkiewicz , Marc Levoy

Proceedings of the 2001 symposium on Interactive 3D graphics March 2001

**14** Systems & applications I: Eye gaze correction for 80%



videoconferencing

Jason Jerald , Mike Daily

Proceedings of the symposium on ETRA 2002: eye tracking research & applications symposium March 2002

This paper describes a 2D videoconferencing system with eye gaze correction. Tracking the eyes and warping the eyes appropriately each frame appears to create natural eye contact between users. The geometry of the eyes as well as the displacement of the camera with the remote user's image determines the warp. We implement this system within software, not requiring any specialized hardware.

**15** Sort-last parallel rendering: Parallel rendering with k-way 80%



replication

Rudrajit Samanta , Thomas Funkhouser , Kai Li

Proceedings of the IEEE 2001 symposium on parallel and large-data visualization and graphics October 2001

With the recent advances in commodity graphics hardware performance, PC clusters have become an attractive alternative to traditional high-end graphics workstations. The main challenge is to develop parallel rendering algorithms that work well within the memory constraints and communication limitations of a

networked cluster. Previous systems have required the entire 3D scene to be replicated in memory on every PC. While this approach can take advantage of view-dependent load balancing algorithm ...

**16** Exploiting Video: Spatially-encoded far-field representations for interactive walkthroughs 80%



Andrew Wilson , Ketan Mayer-Patel , Dinesh Manocha

Proceedings of the ninth ACM international conference on Multimedia October 2001

We introduce the notion of spatially encoded video and use it for efficiently representing image-based impostors for interactive walkthroughs. As part of a pre-process, we automatically decompose the model and compute the far-fields. The resulting texture images are organized along multiple dimensions and can be accessed in a user-steered order at interactive rates. Our encoding algorithm can compress the impostors size by two orders of magnitude. Furthermore, the storage cost for additional imp ...

**17** Perception-guided global illumination solution for animation rendering 80%



Karol Myszkowski , Takehiro Tawara , Hiroyuki Akamine , Hans-Peter Seidel

Proceedings of the 28th annual conference on Computer graphics and interactive techniques August 2001

We present a method for efficient global illumination computation in dynamic environments by taking advantage of temporal coherence of lighting distribution. The method is embedded in the framework of stochastic photon tracing and density estimation techniques. A locally operating energy-based error metric is used to prevent photon processing in the temporal domain for the scene regions in which lighting distribution changes rapidly. A perception-based error metric suitable for animation is u ...

**18** Relief texture mapping 80%



Manuel M. Oliveira , Gary Bishop , David McAllister

Proceedings of the 27th annual conference on Computer graphics and

## interactive techniques July 2000

We present an extension to texture mapping that supports the representation of 3-D surface details and view motion parallax. The results are correct for viewpoints that are static or moving, far away or nearby. Our approach is very simple: a relief texture (texture extended with an orthogonal displacement per texel) is mapped onto a polygon using a two-step process: First, it is converted into an ordinary texture using a surprisingly simple 1-D forward transform. The result ...

**19** QSplat: a multiresolution point rendering system for large meshes 80%

Szymon Rusinkiewicz , Marc Levoy

Proceedings of the 27th annual conference on Computer graphics and interactive techniques July 2000

Advances in 3D scanning technologies have enabled the practical creation of meshes with hundreds of millions of polygons. Traditional algorithms for display, simplification, and progressive transmission of meshes are impractical for data sets of this size. We describe a system for representing and progressively displaying these meshes that combines a multiresolution hierarchy based on bounding spheres with a rendering system based on points. A single data structure is used for view frustum ...

**20** A representation for composition of virtual indoor environment 80%

Hongju Li , Enhua Wu

Proceedings of the ACM symposium on Virtual reality software and technology 1998 November 1998

---

Results 1 - 20 of 142

short listing

  
Prev  
Page

1 2 3 4 5 6 7 8

  
Next  
Page

---

The ACM Portal is published by the Association for Computing Machinery. Copyright © 2003 ACM, Inc.